

BESTFLEX

GRAVITY FLEXIBLE CONVEYORS



Type BFR BESTFLEX with Rollers

- Very robust Construction
- Load capacity : 220 kg/metre
- Castors Ø 127x38 mm
- Standard roller pitch 127mm
Available options : pitch 76 and 102mm
- Bright zinc plated rollers Ø 35mm
- Adjustable height : 720 to 1000 mm

EXAMPLE	Lengths Expanded & Closed
Width 600 mm	4.9 m - 1.7 m 6.1 m - 2.1 m 7.4 m - 2.6 m 9.8 m - 3.4 m Any length available
Width 750 mm	4.9 m - 1.7 m 6.1 m - 2.1 m 7.4 m - 2.6 m 9.8 m - 3.4 m Any length available
Width 900 mm	4.9 m - 1.7 m 6.1 m - 2.1 m 7.4 m - 2.6 m 9.8 m - 3.4 m Any length available



Type BF/200 BESTFLEX with Skatewheels

- Very robust Construction
- Load capacity : 300 kg/metre
- Castors Ø 127x38 mm
- Standard roller pitch 127mm
Available options : pitch 76 and 102mm
- Zinc plated or plastic skatewheels Ø 48mm
- Adjustable height : 720 to 1000 mm

EXAMPLE	Lengths Expanded & Closed
Width 600 mm	4.9 m - 1.3 m 6.1 m - 1.6 m 7.4 m - 2 m 9.8 m - 2.6 m Any length available
Width 750 mm	4.9 m - 1.3 m 6.1 m - 1.6 m 7.4 m - 2 m 9.8 m - 2.6 m Any length available
Width 900 mm	4.9 m - 1.3 m 6.1 m - 1.6 m 7.4 m - 2 m 9.8 m - 2.6 m Any length available



C O N V E Y O R S

A DURAVANT COMPANY



Exclusive distributor
for the Benelux & France

UVO Tec BV

FMH CONVEYORS Benelux & France

Tel : +32.3.455.43.22 - Fax : + 32.3.454.36.70

Email : info@uvotec.eu www.uvotec.eu

WE HAVE SPECIFIC SOLUTIONS FOR YOUR APPLICATION